

KEY FEATURES

Modem

- .V.92 (up to 56 KBPS download, 48 KBPS upload)
- .V.90 (up to 56 KBPS download, 33 KBPS upload)
- .V.34 (4.8 KBPS to 33.6 KBPS)
- .V.32 bis (4.8 KBPS to 14.4 KBPS)
- .V.23 bis (75 BPS to 1.2 KBPS)
- .V.22 bis (50 BPS to 2.4 KBPS)
- .V.21, Bell 103/Bell 212
- .Auto mode
- .V.44/V.42 bis / MNP 5 data compression
- .V.42/MNP 2-4 error correction
- .V.29 Diagnostic
- .Hayes AT Command set
- .TIES escape code
- .Quick Connect (V.92)

FAX

- .Group3, Class 1
- .V.17
- .V.27 ter

Telephony Services

- .Wake up on Ring
- .Ring detection

.On/Off hook control

.Call progress monitor

.DTMF detection and generation

fax/modem distinction

.Caller ID (optional)

.Modem on Hold (V.92)

Video conferencing

.V.80/H.324 interface support

Operating System Support

.Windows (98/98SE/ME/2000/XP)

Power Consumption

. $<70 \pm 0.5\text{mA}$ Operating Mode

. $<3 \pm 0.5\text{mA}$ Stand-by

Diagnostic Tool

.Modem Helper